




TECHNICAL DATA SHEET

CRYPTO HEAVY-DUTY PDU



C14 plug locking mechanism and P-LOCK and V-Lock power cord compatible

C20 P-LOCK and V-Lock power cord compatible

FEATURES

Unit designed to handle 48 S9 miners or similar load

INPUT

VOLTAGE	400V
LOAD CURRENT	128A
INPUT CONECTOR	Hard Wire terminal block up to 35mm ² wire
FREQUENCY	50 Hz

OUTPUT

OUTLET TYPE	IEX (C13/C19) combo with power cord retention - 24 banks (16A rated) of 2xIEX outlets
PROTECTIONS	24 single pole 16A hydraulic magentic breaker (1 breaker x bank)
MAX POWER	1840 Watt x outlet

CHASSIS ENCLOSURE

CHASSIS TYPE	0U rack or shelf mount
DIMENSIONS (W x D x H)	1820 x 111,5 x 90 mm
COLOR	Black RAL9005 powder coating

OPERATING ENVIRONMENTAL

TEMPERATURE RANGE	0° to 60° C (30° to 140° F)
HUMIDITY	0 - 95 %
ELEVATION	0 - 4000 Meters

CONFORMANCE

IEC 60950-1:2005 (Sec ond Edition) + Am 1:2009 + Am 2:2013



TECHNICAL DATA SHEET

CRYPTO HEAVY-DUTY PDU

ELECTRICAL SCHEMATIC

